



Product picture shows an exemplary solution for the temperature range +2 °C to +8 °C

## DESCRIPTION

Ensure patient-safe medicines and accurate clinical trial results with ProofPak. Our innovative, reusable thermal packaging ensures precise temperature control from -70°C to +37°C, unaffected by seasons or climate. Qualified according to ISTA 7D standards, ProofPak ensures consistent reliability, safeguarding your temperature-sensitive pharmaceuticals from production through to delivery. Experience seamless logistics with 'ready to load & go', giving you time to focus on advancing your clinical research while we protect your products with unmatched precision and reliability.

Note: This product shall be stored and transported in upright position!

## DIMENSIONS AND WEIGHT

External Dimensions (l x w x h) [mm] [inch]		Internal Dimensions <sup>1</sup> (l x w x h) [mm] [inch]		Tolerances [mm] [inch]	
555 x 560 x 555	21.9 x 22 x 21.9	355 x 355 x 360	14 x 14 x 14.2	± 5	± 0.2

Tare Weight <sup>1</sup> [kg] [lbs]		Payload <sup>1</sup> (Volume) [L]	
45.3 ± 1	99.9 ± 2.2		45

<sup>1</sup>including Dry Ice

## DRY ICE CONFIGURATION

Dry Ice compartment	Dry Ice pellet diameter [mm] [inch]		Weight [kg] [lbs]	
Upper compartment	3	0.1	11	24.3
Side compartments	3	0.1	21	46.3

## PERFORMANCE The ProofPak 74 Dry Ice is qualified in the temperature range below -60 °C

Temperature scenario	Duration [hrs]	Kelvin-hours <sup>2</sup>	Average ambient temperature [°C]
ISTA 7D summer	≥ 144	≥ 15091	+29.8

<sup>2</sup>Detailed information about the concept of Kelvin-hours on [www.kelvinhours.com](http://www.kelvinhours.com)

For more details, please view the qualification report. Before performing a shipment with the ProofPak 74 Dry Ice it is suggested that the user performs a validation process with the equipment available and under the conditions available. A test in worst case conditions is recommended. The box provides a very stable and well-designed system solution which has to be adapted on the particular requirements of the user.

For more information please contact [support@envirotainer.com](mailto:support@envirotainer.com).