



Product picture shows an exemplary solution for the temperature range +2 °C to +8 °C

DESCRIPTION

Specifically designed for door-to-door pharmaceutical distribution of smaller volumes to remote locations, OnePak ensures your products reach even the most inaccessible areas without compromising quality or efficacy. This single-use solution is ideal for regions with limited logistics services, eliminating the need for return shipping and ensuring consistent access to medicines.

DIMENSIONS AND WEIGHT

External Dimensions (l x w x h) [mm] [inch]		Internal Dimensions ¹ (l x w x h) [mm] [inch]		Tolerances [mm] [inch]	
575 x 465 x 480	22.6 x 18.3 x 18.9	420 x 320 x 320	16.5 x 12.6 x 12.6	± 5	± 0.2
Tare Weight ¹ [kg]		Payload ¹ (Volume) [L]			
16.5 ± 1	36.4 ± 2.2			43	

¹including Temperature Batteries

TEMPERATURE BATTERY CONFIGURATION

OneBlok	Pieces	Dimensions ² (l x w x h) [mm] [inch]		Weight [kg] [lbs]		Material number
44342	4	442 x 342 x 23	17.4 x 13.5 x 0.9	2	4.4	AK000480
34342	2	342 x 342 x 23	13.5 x 13.5 x 0.9	1.5	3.3	AK000479

²dimensions of empty Temperature Battery shell, variation due to PCM inside and aggregation state possible

PERFORMANCE The OnePak 43 +22G EL is qualified in the temperature range from +15 °C to +25 °C

Temperature scenario	Duration [hrs]	Kelvin-hours ³	Average ambient temperature [°C]
ISTA 7D summer	≥ 139	≥ 1418	+30.2
ISTA 7D winter	≥ 136	≤ -1999	+5.3

³Detailed information about the concept of Kelvin-hours on www.kelvinhours.com

For more details, please view the qualification report. Before performing a shipment with the OnePak 43 +22G EL it is suggested that the user performs a validation process with the equipment available and under the conditions available. A test in worst case conditions is recommended. The box provides a very stable and well-designed system solution which has to be adapted on the particular requirements of the user.

For more information please contact support@envirotainer.com.