



Product picture shows an exemplary solution for the temperature range +2 °C to +8 °C

## DESCRIPTION

Specifically designed for door-to-door pharmaceutical distribution of smaller volumes to remote locations, OnePak ensures your products reach even the most inaccessible areas without compromising quality or efficacy. This single-use solution is ideal for regions with limited logistics services, eliminating the need for return shipping and ensuring consistent access to medicines.

**DIMENSIONS AND WEIGHT**

External Dimensions (l x w x h)		Internal Dimensions <sup>1</sup> (l x w x h)		Tolerances	
[mm]	[inch]	[mm]	[inch]	[mm]	[inch]
360 x 345 x 370	14.2 x 13.6 x 14.6	165 x 165 x 165	6.5 x 6.5 x 6.5	± 5	± 0.2

Tare Weight <sup>1</sup>		Payload <sup>1</sup> (Volume)	
[kg]	[lbs]	[L]	
9.6 ± 1	21.2 ± 2.2	4	

<sup>1</sup>Including Temperature Batteries

**TEMPERATURE BATTERY CONFIGURATION**

va-Q-pad	Pieces	Dimensions <sup>2</sup> (l x w x h)		Weight		Material number
		[mm]	[inch]	[kg]	[lbs]	
20204 +22G	6	200 x 200 x 39	7.9 x 7.9 x 1.5	1.2	2.6	AK000235

<sup>2</sup>dimensions of empty Temperature Battery shell, variation due to PCM inside and aggregation state possible

**PERFORMANCE** The OnePak 4 +22G is qualified in the temperature range from +15 °C to +25 °C

Temperature scenario	Duration [hrs]	Kelvin-hours <sup>3</sup>	Average ambient temperature [°C]
ISTA 7D summer	≥ 136	≥ 1346	+29.9
ISTA 7D winter	≥ 120	≤ -1824	+4.8

<sup>3</sup>Detailed information about the concept of Kelvin-hours on [www.kelvinhours.com](http://www.kelvinhours.com)

For more details, please view the qualification report. Before performing a shipment with the OnePak 4 +22G it is suggested that the user performs a validation process with the equipment available and under the conditions available. A test in worst case conditions is recommended. The box provides a very stable and well-designed system solution which has to be adapted on the particular requirements of the user.

For more information please contact [support@envirotainer.com](mailto:support@envirotainer.com).



Product picture shows an exemplary solution for the temperature range +2 °C to +8 °C

## DESCRIPTION

Specifically designed for door-to-door pharmaceutical distribution of smaller volumes to remote locations, OnePak ensures your products reach even the most inaccessible areas without compromising quality or efficacy. This single-use solution is ideal for regions with limited logistics services, eliminating the need for return shipping and ensuring consistent access to medicines.

## DIMENSIONS AND WEIGHT

External Dimensions (l x w x h)		Internal Dimensions <sup>1</sup> (l x w x h)		Tolerances	
[mm]	[inch]	[mm]	[inch]	[mm]	[inch]
360 x 345 x 370	14.2 x 13.6 x 14.6	165 x 165 x 165	6.5 x 6.5 x 6.5	± 5	± 0.2

  

Tare Weight <sup>1</sup>		Payload <sup>1</sup> (Volume)
[kg]	[lbs]	[L]
9 ± 1	19.8 ± 2.2	4

<sup>1</sup>Including Temperature Batteries

## TEMPERATURE BATTERY CONFIGURATION

va-Q-pad	Pieces	Dimensions <sup>2</sup> (l x w x h)		Weight		Material number
		[mm]	[inch]	[kg]	[lbs]	
20204 +05G EL	6	200 x 200 x 39	7.9 x 7.9 x 1.5	1.1	2.4	AK000448

<sup>2</sup>dimensions of empty Temperature Battery shell, variation due to PCM inside and aggregation state possible

## PERFORMANCE The OnePak 4 +05G EL is qualified in the temperature range from +2 °C to +8 °C

Temperature scenario	Duration [hrs]	Kelvin-hours <sup>3</sup>	Average ambient temperature [°C]
ISTA 7D summer	≥ 127	≥ 3175	+30
ISTA 7D winter	> 144	n.a.	+5

<sup>3</sup>Detailed information about the concept of Kelvin-hours on [www.kelvinhours.com](http://www.kelvinhours.com)

For more details, please view the qualification report. Before performing a shipment with the OnePak 4 +05G EL it is suggested that the user performs a validation process with the equipment available and under the conditions available. A test in worst case conditions is recommended. The box provides a very stable and well-designed system solution which has to be adapted on the particular requirements of the user.

For more information please contact [support@envirotainer.com](mailto:support@envirotainer.com).



Product picture shows an exemplary solution for the temperature range +2 °C to +8 °C

## DESCRIPTION

Specifically designed for door-to-door pharmaceutical distribution of smaller volumes to remote locations, OnePak ensures your products reach even the most inaccessible areas without compromising quality or efficacy. This single-use solution is ideal for regions with limited logistics services, eliminating the need for return shipping and ensuring consistent access to medicines.

**DIMENSIONS AND WEIGHT**

External Dimensions (l x w x h)		Internal Dimensions <sup>1</sup> (l x w x h)		Tolerances	
[mm]	[inch]	[mm]	[inch]	[mm]	[inch]
360 x 345 x 370	14.2 x 13.6 x 14.6	165 x 165 x 165	6.5 x 6.5 x 6.5	± 5	± 0.2

Tare Weight <sup>1</sup>		Payload <sup>1</sup> (Volume)
[kg]	[lbs]	[L]
12.4 ± 1	27.3 ± 2.2	4

<sup>1</sup>Including Temperature Batteries

**TEMPERATURE BATTERY CONFIGURATION**

va-Q-pad	Pieces	Dimensions <sup>2</sup> (l x w x h)		Weight		Material number
		[mm]	[inch]	[kg]	[lbs]	
20204 -21G	6	200 x 200 x 39	7.9 x 7.9 x 1.5	1.6	3.5	AK000248

<sup>2</sup>dimensions of empty Temperature Battery shell, variation due to PCM inside and aggregation state possible

**PERFORMANCE** The OnePak 4 -21G is qualified in the temperature range from -25 °C to -15 °C

Temperature scenario	Duration [hrs]	Kelvin-hours <sup>3</sup>	Average ambient temperature [°C]
ISTA 7D summer	≥ 115	≥ 5773	+30.2

<sup>3</sup>Detailed information about the concept of Kelvin-hours on [www.kelvinhours.com](http://www.kelvinhours.com)

For more details, please view the qualification report. Before performing a shipment with the OnePak 4 -21G it is suggested that the user performs a validation process with the equipment available and under the conditions available. A test in worst case conditions is recommended. The box provides a very stable and well-designed system solution which has to be adapted on the particular requirements of the user.

For more information please contact [support@envirotainer.com](mailto:support@envirotainer.com).



Product picture shows an exemplary solution for the temperature range +2 °C to +8 °C

## DESCRIPTION

Specifically designed for door-to-door pharmaceutical distribution of smaller volumes to remote locations, OnePak ensures your products reach even the most inaccessible areas without compromising quality or efficacy. This single-use solution is ideal for regions with limited logistics services, eliminating the need for return shipping and ensuring consistent access to medicines.

**DIMENSIONS AND WEIGHT**

External Dimensions (l x w x h)		Internal Dimensions <sup>1</sup> (l x w x h)		Tolerances	
[mm]	[inch]	[mm]	[inch]	[mm]	[inch]
360 x 345 x 370	14.2 x 13.6 x 14.6	165 x 165 x 165	6.5 x 6.5 x 6.5	± 5	± 0.2

Tare Weight <sup>1</sup>		Payload <sup>1</sup> (Volume)
[kg]	[lbs]	[L]
11.6 ± 1	25.6 ± 2.2	4

<sup>1</sup>Including Temperature Batteries

**TEMPERATURE BATTERY CONFIGURATION**

va-Q-pad	Pieces	Dimensions <sup>2</sup> (l x w x h)		Weight		Material number
		[mm]	[inch]	[kg]	[lbs]	
20204 -26G	6	200 x 200 x 39	7.9 x 7.9 x 1.5	1.5	3.3	AK000415

<sup>2</sup>dimensions of empty Temperature Battery shell, variation due to PCM inside and aggregation state possible

**PERFORMANCE** The OnePak 4 -26G is qualified in the temperature range below -20 °C

Temperature scenario	Duration [hrs]	Kelvin-hours <sup>3</sup>	Average ambient temperature [°C]
ISTA 7D summer	≥ 109	≥ 6005	+30.1

<sup>3</sup>Detailed information about the concept of Kelvin-hours on [www.kelvinhours.com](http://www.kelvinhours.com)

For more details, please view the qualification report. Before performing a shipment with the OnePak 4 -26G it is suggested that the user performs a validation process with the equipment available and under the conditions available. A test in worst case conditions is recommended. The box provides a very stable and well-designed system solution which has to be adapted on the particular requirements of the user.

For more information please contact [support@envirotainer.com](mailto:support@envirotainer.com).





Product picture shows an exemplary solution for the temperature range +2 °C to +8 °C

## DESCRIPTION

Specifically designed for door-to-door pharmaceutical distribution of smaller volumes to remote locations, OnePak ensures your products reach even the most inaccessible areas without compromising quality or efficacy. This single-use solution is ideal for regions with limited logistics services, eliminating the need for return shipping and ensuring consistent access to medicines.

**DIMENSIONS AND WEIGHT**

External Dimensions (l x w x h)		Internal Dimensions <sup>1</sup> (l x w x h)		Tolerances	
[mm]	[inch]	[mm]	[inch]	[mm]	[inch]
360 x 345 x 370	14.2 x 13.6 x 14.6	165 x 165 x 165	6.5 x 6.5 x 6.5	± 5	± 0.2

Tare Weight <sup>1</sup>		Payload <sup>1</sup> (Volume)
[kg]	[lbs]	[L]
13.4 ± 1	29.5 ± 2.2	4

<sup>1</sup>Including Temperature Batteries

**TEMPERATURE BATTERY CONFIGURATION**

va-Q-pad	Pieces	Dimensions <sup>2</sup> (l x w x h)		Weight		Material number
		[mm]	[inch]	[kg]	[lbs]	
20204 -37G	6	200 x 200 x 39	7.9 x 7.9 x 1.5	1.8	4	AK000436

<sup>2</sup>dimensions of empty Temperature Battery shell, variation due to PCM inside and aggregation state possible

**PERFORMANCE** The OnePak 4 -37G is qualified in the temperature range from 0 °C to -30 °C

Temperature scenario	Duration [hrs]	Kelvin-hours <sup>3</sup>	Average ambient temperature [°C]
ISTA 7D summer	≥ 81	≥ 5249	+29.8

<sup>3</sup>Detailed information about the concept of Kelvin-hours on [www.kelvinhours.com](http://www.kelvinhours.com)

For more details, please view the qualification report. Before performing a shipment with the OnePak 4 -37G it is suggested that the user performs a validation process with the equipment available and under the conditions available. A test in worst case conditions is recommended. The box provides a very stable and well-designed system solution which has to be adapted on the particular requirements of the user.

For more information please contact [support@envirotainer.com](mailto:support@envirotainer.com).