

OnePak 43 +05G EL (Article number: BC000722)

[va-Q-one 43 +05G EL]

For +2 °C to +8 °C shipments

Envirotainer°

Precision with Purpose



Product picture shows an exemplary solution for the temperature range +2 °C to +8 °C

DESCRIPTION

Specifically designed for door-to-door pharmaceutical distribution of smaller volumes to remote locations, OnePak ensures your products reach even the most inaccessible areas without compromising quality or efficacy. This single-use solution is ideal for regions with limited logistics services, eliminating the need for return shipping and ensuring consistent access to medicines.

DIMENSIONS AND WEIGHT

External Dimensions (l x w x h)		Internal Dimensions ¹ (l x w x h)		Tolerances	
[mm]	[inch]	[mm]	[inch]	[mm]	[inch]
575 x 465 x 480	22.6 x 18.3 x 18.9	420 x 320 x 320	16.5 x 12.6 x 12.6	± 5	± 0.2
Tare Weight ¹			Payload ¹ (Volume)		
[kg]	[lbs]		[L]		
16.5 ± 1	36.4 ± 2.2		43		

¹Including Temperature Batteries

TEMPERATURE BATTERY CONFIGURATION

OneBlok	Pieces	Dimensions ² (l x w x h)		Weight		Material number
		[mm]	[inch]	[kg]	[lbs]	
44342 +05G EL	4	435 x 335 x 19	17.1 x 13.2 x 0.7	1.9	4.2	AK000452
34342 +05G EL	2	335 x 335 x 19	13.2 x 13.2 x 0.7	1.6	3.5	AK000451

²dimensions of empty Temperature Battery shell, variation due to PCM inside and aggregation state possible

PERFORMANCE The OnePak 43 +05G EL is qualified in the temperature range from +2 °C to +8 °C

Temperature scenario	Duration [hrs]	Kelvin-hours ³	Average ambient temperature [°C]
ISTA 7D summer	≥ 103	≥ 2565	+29.9
ISTA 7D winter	> 144	n.a.	+4.6

³Detailed information about the concept of Kelvin-hours on www.kelvinhours.com

For more details, please view the qualification report. Before performing a shipment with the OnePak 43 +05G EL it is suggested that the user performs a validation process with the equipment available and under the conditions available. A test in worst case conditions is recommended. The box provides a very stable and well-designed system solution which has to be adapted on the particular requirements of the user.

For more information please contact support@envirotainer.com.