



## DESCRIPTION

Leading the way in innovation, the RelEye® family is designed to meet the strictest requirements in pharmaceutical air freight. With up to 170 hours of autonomy, without the need for recharging, RelEye® maintains the temperature for longer than any other available active solution, ensuring that your product's temperature and efficacy remains unaffected even during unexpected delays. With 18 built-in sensors, the Live Monitoring and Control Tower services safeguard the efficacy of your products, providing instant visibility into shipment conditions throughout its journey.

The RelEye® RAP is our highest-capacity solution, offering the best efficiency for your commercial shipments. With space for 5 Euro pallets (4 US pallets), it features the industry's largest internal volume, allowing you to consolidate more cargo per shipment. This translates to significant savings on total landed cost and a reduced environmental impact. The integrated Live Monitoring provides precise real time visibility of your shipment at every stage of transit, while access to the Control Tower enables our expert team to proactively intervene if an unexpected event arises.

DIMENSIONS AND WEIGHT

External Dimensions (l x w x h)		Internal Dimensions (l x w x h)		Door Opening (w x h)	
[mm]	[inch]	[mm]	[inch]	[mm]	[inch]
3175 x 2235 x 1626	125 x 88 x 64	2466 x 2055 x 1320	97.1 x 80.9 x 52	2055 x 1320	80.9 x 52
Tare Weight		Max. Gross Weight		Max. Net Weight	
[kg]	[lbs]	[kg]	[lbs]	[kg]	[lbs]
1100	2425.1	4625	10196.4	3525	7771.3

REFRIGERATING SYSTEM

Power Rating	IP Rating	Container Set Temperature Options	Temperature Control Accuracy
100-240 V AC, 50-60 Hz, Max 16 A	IP15B	+4°C to +30°C (+39.2°F to +86°F)	±2°C for set point 5°C, ±3°C for set point 20°C

PERFORMANCE The RelEye RAP is qualified in the temperature range from +2 °C to +8 °C

Autonomy	Charging Time
170h at +20°C (+68°F) ambient	11h (0 - 100%, 230 V)

LIVE MONITORING CAPABILITIES

8 Cargo space temperatures [°C] Cargo loaded inside [Yes / No] 2 Ambient temperatures [°C] Door openings [Open / Closed]	Cargo space humidity [RH %] Battery level [%] Ambient humidity [RH %] GPS location
---	---

OTHER INFORMATION

Suitable for use on aircraft A300, A310, A330, A340, A380, B747, B767, B777, DC10, IL86, MD11, L1011. For other aircrafts, alternative operating procedures may apply. For other aircrafts, alternative operating procedures may apply. Forkliftable with slot-height 93 mm (3.7 inch), slot-width 355 mm (14 inch) and slot center to center distance 852 mm (33.5 inch).

CODES

IATA ULD Type Code	ATA Code	AS36100 Identifier
RAP	LD-09	2A8C

For more information please contact [support@envirotainer.com](mailto:support@envirotainer.com).